

## External Retaining Rings

### 轴用挡圈



For OD	Dia.	Wd.	ID	Thick.	Hardness
	baisc	baisc	baisc	baisc	Min.
1/4"	0.23"	0.029"	0.225"	0.025"	Rockwell C40
9/32"	0.261"	0.029"	0.256"	0.025"	Rockwell C40
5/16"	0.29"	0.029"	0.281"	0.025"	Rockwell C40
11/32"	0.321"	0.029"	0.309"	0.025"	Rockwell C40
3/8"	0.352"	0.029"	0.338"	0.025"	Rockwell C40
13/32"	0.382"	0.029"	0.366"	0.025"	Rockwell C40
7/16"	0.412"	0.029"	0.395"	0.025"	Rockwell C40
15/32"	0.443"	0.029"	0.428"	0.025"	Rockwell C40
1/2"	0.468"	0.039"	0.461"	0.035"	Rockwell C40
9/16"	0.53"	0.039"	0.521"	0.035"	Rockwell C40
19/32"	0.559"	0.039"	0.55"	0.035"	Rockwell C40
5/8"	0.588"	0.039"	0.579"	0.035"	Rockwell C40
11/16"	0.646"	0.046"	0.635"	0.042"	Rockwell C40
3/4"	0.704"	0.046"	0.693"	0.042"	Rockwell C40
25/32"	0.733"	0.046"	0.722"	0.042"	Rockwell C40
13/16"	0.762"	0.046"	0.751"	0.042"	Rockwell C40
27/32"	0.791"	0.046"	0.78"	0.042"	Rockwell C47
7/8"	0.821"	0.046"	0.81"	0.042"	Rockwell C40
15/16"	0.882"	0.046"	0.867"	0.042"	Rockwell C40
63/64"	0.926"	0.046"	0.91"	0.042"	Rockwell C40
1"	0.94"	0.046"	0.925"	0.042"	Rockwell C40
1 1/16"	0.998"	0.056"	0.982"	0.05"	Rockwell C40
1 1/8"	1.059"	0.056"	1.041"	0.05"	Rockwell C40
1 3/16"	1.118"	0.056"	1.098"	0.05"	Rockwell C40
1 1/4"	1.176"	0.056"	1.156"	0.05"	Rockwell C40
1 5/16"	1.232"	0.056"	1.214"	0.05"	Rockwell C40
1 3/8"	1.291"	0.056"	1.272"	0.05"	Rockwell C40
1 7/16"	1.35"	0.056"	1.333"	0.05"	Rockwell C40
1 1/2"	1.406"	0.056"	1.387"	0.05"	Rockwell C40
1 9/16"	1.468"	0.068"	1.446"	0.062"	Rockwell C40
1 5/8"	1.529"	0.068"	1.503"	0.062"	Rockwell C40
1 11/16"	1.589"	0.068"	1.56"	0.062"	Rockwell C40
1 3/4"	1.65"	0.068"	1.618"	0.062"	Rockwell C40
1 13/16"	1.708"	0.068"	1.618"	0.062"	Rockwell C40
1 7/8"	1.769"	0.068"	1.735"	0.062"	Rockwell C40
1 31/32"	1.857"	0.068"	1.85"	0.062"	Rockwell C47

2"	2 1/16"	0.068"	1.85"	0.062"	Rockwell C40
2 1/16"	1.946"	0.086"	1.906"	0.078"	Rockwell C40
2 1/8"	2.003"	0.086"	1.964"	0.078"	Rockwell C40
2 5/32"	2.032"	0.086"	1.993"	0.078"	Rockwell C40
2 1/4"	2.12"	0.086"	2.081"	0.078"	Rockwell C40
2 5/16"	2.178"	0.086"	2.139"	0.078"	Rockwell C40
2 3/8"	2.239"	0.086"	2.197"	0.078"	Rockwell C40
2 7/16"	2.299"	0.086"	2.197"	0.078"	Rockwell C40
2 1/2"	2.36"	0.086"	2.313"	0.078"	Rockwell C40
2.559"	2.419"	0.086"	2.377"	0.078"	Rockwell C47
2 5/8"	2.481"	0.086"	2.428"	0.078"	Rockwell C40
2 11/16"	2.541"	0.086"	2.485"	0.078"	Rockwell C40
2 3/4"	2.602"	0.103"	2.543"	0.093"	Rockwell C40
2 7/8"	2.721"	0.103"	2.659"	0.093"	Rockwell C40
2 15/16"	2.779"	0.103"	2.717"	0.093"	Rockwell C40
3"	2.838"	0.103"	2.775"	0.093"	Rockwell C40
3 1/16"	2.898"	0.103"	2.832"	0.093"	Rockwell C47
3 1/8"	2.957"	0.103"	2.892"	0.093"	Rockwell C40
3 5/32"	2.986"	0.103"	2.92"	0.093"	Rockwell C47
3 1/4"	3.076"	0.103"	3.006"	0.093"	Rockwell C40
3 11/32"	3.166"	0.103"	3.092"	0.093"	Rockwell C47
3 1/2"	3.316"	0.12"	3.237"	0.109"	Rockwell C40
3.543"	3.357"	0.12"	3.237"	0.109"	Rockwell C44
3 5/8"	3.435"	0.12"	3.352"	0.109"	Rockwell C40
3 11/16"	3.493"	0.12"	3.41"	0.109"	Rockwell C44
3 3/4"	3.552"	0.12"	3.468"	0.109"	Rockwell C40
3 7/8"	3.673"	0.12"	3.584"	0.109"	Rockwell C40
3 15/16"	3.493"	0.12"	3.41"	0.109"	Rockwell C44
4 "	3.972"	0.12"	3.7"	0.109"	Rockwell C40
4 1/8"	3.915"	0.12"	3.8"	0.109"	Rockwell C40
4 1/4"	4.065"	0.12"	3.989"	0.109"	Rockwell C40
4 3/8"	4.19"	0.12"	4.106"	0.109"	Rockwell C40
4 1/2"	4.31"	0.12"	4.223"	0.109"	Rockwell C40
4 3/4"	4.55"	0.12"	4.458"	0.109"	Rockwell C40
5"	4.79"	0.12"	4.692"	0.109"	Rockwell C40
5 1/4"	5.03"	0.139"	0.139"	0.125"	Rockwell C44
5 1/2"	5.265"	0.139"	5.162"	0.125"	Rockwell C40
5 3/4"	5.505"	0.139"	5.396"	0.125"	Rockwell C44
6"	5.745"	0.139"	5.631"	0.125"	Rockwell C40
6 1/4"	5.985"	0.174"	5.866"	0.156"	Rockwell C44
6 1/2"	6.225"	0.174"	5.866"	0.156"	Rockwell C40
6 3/4"	6.465"	0.174"	6.335"	0.156"	Rockwell C44
7"	6.705"	0.174"	6.57"	0.156"	Rockwell C40
7 1/2"	7.18"	0.209"	7.009"	0.187"	Rockwell C40
8"	7.66"	0.209"	7.478"	0.187"	Rockwell C40
8 1/2"	8.14"	0.209"	7.947"	0.187"	Rockwell C40
9"	8.62"	0.209"	8.415"	0.187"	Rockwell C40
10"	9.575"	0.209"	9.355"	0.187"	Rockwell C40