

High Alloy Split Lock Washers 高合金分体锁紧垫圈



Size	A		B	T	W	BW
	max	min	max	min	min	min
#2	0.094	0.088	0.172	0.02	0.035	0.024
#3	0.107	0.101	0.195	0.025	0.04	0.028
#4	0.12	0.114	0.209	0.025	0.04	0.028
#5	0.133	0.127	0.236	0.031	0.047	0.033
#6	0.148	0.141	0.25	0.031	0.047	0.033
#8	0.174	0.167	0.293	0.04	0.055	0.038
#10	0.2	0.193	0.334	0.047	0.062	0.043
#12	0.227	0.22	0.377	0.056	0.07	0.049
1/4	0.26	0.252	0.487	0.062	0.109	0.076
5/16	0.322	0.314	0.583	0.078	0.125	0.087
3/8	0.385	0.377	0.68	0.094	0.141	0.099
7/16	0.45	0.44	0.776	0.109	0.156	0.109
1/2	0.512	0.502	0.869	0.125	0.171	0.12
9/16	0.574	0.564	0.965	0.141	0.188	0.132
5/8	0.641	0.628	1.073	0.156	0.203	0.142
3/4	0.766	0.753	1.265	0.188	0.234	0.164
7/8	0.894	0.878	1.459	0.219	0.266	0.186
1	1.024	1.003	1.656	0.25	0.297	0.208
1-1/8	1.153	1.129	1.847	0.281	0.328	0.23
1-1/4	1.28	1.254	2.036	0.312	0.359	0.251
1-3/8	1.408	1.379	2.219	0.344	0.391	0.274
1-1/2	1.534	1.504	2.419	0.375	0.422	0.295
1-5/8	1.663	1.633	2.553	0.389	0.424	0.297
1-3/4	1.789	1.758	2.679	0.389	0.424	0.297
1-7/8	1.914	1.883	2.811	0.422	0.427	0.299
2	2.039	2.008	2.936	0.422	0.427	0.299
2-1/4	2.293	2.262	3.221	0.44	0.442	0.309
2-1/2	2.543	2.512	3.471	0.44	0.442	0.309
2-3/4	2.793	2.762	3.824	0.458	0.491	0.344
3	3.043	3.012	4.074	0.458	0.491	0.344