

## High Collar Split Lock Washers

### 高领开口锁紧垫圈



Size	A		B	T	W	BW	per 1000 units
	Max	Min	max	min	min	min	kg
NO.4(0.112)	0.12	0.114	0.173	0.022	0.022	0.0115	0.038
NO.5(0.125)	0.133	0.127	0.202	0.03	0.03	0.021	0.075
NO.6(0.138)	0.148	0.141	0.216	0.03	0.03	0.021	0.081
NO.8(0.164)	0.174	0.167	0.267	0.047	0.042	0.029	0.206
NO.10(0.19)	0.2	0.193	0.294	0.047	0.043	0.029	0.233
1/4	0.26	0.252	0.363	0.078	0.047	0.033	0.538
5/16	0.322	0.314	0.457	0.093	0.062	0.043	1.035
3/8	0.385	0.377	0.55	0.125	0.076	0.053	2.024
7/16	0.45	0.44	0.644	0.14	0.09	0.063	3.126
1/2	0.512	0.502	0.733	0.172	0.103	0.072	4.955
5/8	0.641	0.628	0.917	0.203	0.125	0.087	9.153
3/4	0.766	0.753	1.105	0.218	0.154	0.108	14.397
7/8	0.894	0.878	1.291	0.234	0.182	0.127	21.167
1	1.024	1.003	1.478	0.25	0.208	0.146	29.751
1-1/8	1.153	1.129	1.663	0.313	0.236	0.165	47.124
1-1/4	1.28	1.254	1.79	0.313	0.236	0.165	51.57
1-3/8	1.408	1.379	2.031	0.375	0.292	0.204	84.193
1-1/2	1.534	1.504	2.159	0.375	0.292	0.204	90.855
1-3/4	1.789	1.758	2.596	0.469	0.383	0.268	172.801
2	2.039	2.008	2.846	0.469	0.383	0.268	192.645
2-1/4	2.293	2.262	3.345	0.508	0.508	0.356	311.504
2-1/2	2.543	2.512	3.595	0.508	0.508	0.356	339.282
2-3/4	2.793	2.762	4.095	0.633	0.633	0.443	584.263
3	3.043	3.012	4.345	0.633	0.633	0.443	626.867